



Single Cylinder 5hp Air Cooled Diesel Engine GET173F GET178F GET186FA

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Single Cylinder, Vertical, Four-stroke, Direct Injection, Air-cooled
- Borexstroke: 73x59mm, 78x62mm, 86x72mm
- Displacement: 247ml, 296ml, 418ml
- Compression Ratio: 20:01, 20:01, 19:01
- Rated Power(kw/rpm): 3.5/3000-3.8/3600 3.68/3000-4/3600 5.7/3000-6.3/3600
- Rated Power(hp/rpm): 4.8/3000-5.2/3600, 5.0/3000-5.4/3600, 7.8/3000-8.6/3600
- Rated Speed(rpm): 3000/3600
- Lowest Rotation Speed At Zero Load: ≤1300r/min
- Lubricating System: Pressure Splashed
- Starting System: Recoil Start/electric Starter
- Rotation Direction(face To The Output Axle): Anticlockwise
- Fuel Type: 0#(summer) 10#(winter) 25#(chillness)

for more products please visit us on diesenginepumps.com

Product Description

Single Cylinder 5 Hp Air Cooled Diesel Engine GET173F GET178F GET186FA

The engine models you mentioned, GET173F, GET178F, and GET186FA, are examples of single-cylinder, air-cooled diesel engines. These engines are commonly used in various applications such as small generators, water pumps, construction equipment, and agricultural machinery. Here are some key features and specifications of these engines:

GET173F Single Cylinder Air Cooled Diesel Engine:

Displacement: Typically around 242 cc (cubic centimeters)

Power Output: Can range from 4 to 6 horsepower (hp)

Fuel Type: Diesel

Cooling System: Air-cooled

Starting Method: Manual or electric start options may be available

Application: Suitable for smaller power requirements, such as portable generators and lightweight machinery.

GET178F Single Cylinder Air Cooled Diesel Engine:

Displacement: Usually around 296 cc

Power Output: Typically ranges from 6 to 9 hp

Fuel Type: Diesel

Cooling System: Air-cooled

Starting Method: Manual or electric start options may be available

Application: Suitable for medium-sized power needs, including small pumps, compact machinery, and portable generators.

GET186FA Single Cylinder Air Cooled Diesel Engine:

Displacement: Generally around 406 cc

Power Output: Typically ranges from 10 to 13 hp

Fuel Type: Diesel

Cooling System: Air-cooled

Starting Method: Manual or electric start options may be available

Application: Suitable for higher power requirements, including larger generators, construction equipment, and agricultural machinery.

Model	GET188F	GET190F	GET192F	GET195F
Type	Single cylinder, vertical, four-stroke, direct injection, air-cooled	Single cylinder, vertical, four-stroke, direct injection, air-cooled	Single cylinder, vertical, four-stroke, direct injection, air-cooled	Single cylinder, vertical, four-stroke, direct injection, air-cooled
Bore*Stroke	88.75*90mm	75*77mm	92*75mm	95*75mm
Displacement	19:01cc	19:01cc	19:01cc	19:01cc
Compression Ratio	6.7/3000	7.8/3000	6.5/3000	8.1/3000
Rated Power (KWipm)	7.2/3600	7.3/3600	8.2/3600	8.7/3600
Rated Power (HPIIPm)	9.8/3600	10.3/3600	11.2/3600	11.8/3600
Rated Speed (rpm)		3000/3600		
Lowest rotation speed at zero load		1300		
Lubricating system		Pressure splashad	Pressure splashad	Pressure splashad

These engines are designed for reliability, durability, and ease of maintenance. They are known for their fuel efficiency, long lifespan, and ability to handle heavy-duty applications. It's important to note that specific features and specifications may vary depending on the manufacturer and model of the engine. Always refer to the manufacturer's documentation or consult with a knowledgeable professional for detailed information about a particular engine model.

单缸风冷柴油机系列 Single Cylinder Air Cooled Diesel Engine Series



單缸動力參數表 Specifications

[illegible]

Wuxi Guangertai Power Machinery Co.,Ltd

 13813650506

 2415819289@qq.com

 diesenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA