



220V Open Type Diesel Generator 7500E 8500E Diesel Powered Generator

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Output(kw): 1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
- Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- Insulation Grade: F
- Pole Number: 2
- Excitation Mode: Self-excitation & Constant Voltage (AVR)
- Panel Type: General Panel

for more products please visit us on dieselenginepumps.com

Product Description

220V Open Type Diesel Generator GET2500E GET3500E GET6500E GET7500E GET8500E GET9500E

Applications of Open Type Diesel Generators:

Construction Sites: Open type diesel generators are widely used in construction sites to provide temporary power for tools, lighting, and other equipment. They are capable of handling high power demands and can withstand harsh conditions.

Agriculture: Diesel generators are commonly used in agricultural settings, such as on farms or in rural areas, where a reliable power source is required for irrigation systems, machinery, and other agricultural operations.

Remote Locations: Open type diesel generators are ideal for providing power in remote areas where access to the electrical grid is limited or unavailable. They can be used for off-grid cabins, remote research stations, telecommunications towers, and oil or gas exploration sites.

Emergency Backup Power: Open type diesel generators are often employed as backup power sources in residential, commercial, or industrial settings. They can automatically kick in during power outages and provide electricity until the main power supply is restored.

Events and Entertainment: These generators are commonly used at outdoor events, concerts, festivals, and movie sets to power stages, lighting, sound systems, and other event equipment.

It's important to note that open type diesel generators tend to produce more noise compared to their soundproof counterparts. Therefore, their usage should be carefully considered in noise-sensitive areas or situations where noise reduction is a priority.

Rated Output(kw):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ 730x495x630/ 730x495x655
Working Assorting Weight (kg):	66 83 110 115 120 125
Structure Type:	Open Type
Cylinder No. -bore X Stroke (mm):	1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600
Lubrication System:	Pressure Splashed
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 20Ah/ 12V 30Ah
Fuel Tank Capacity (L):	13.5
Rated Frequency:	50hz 60hz
Max Output (kw):	2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
Rated Current (A):	7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	53 70 100 105 110 115
Noise Level (7m):	77 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	247 296 418 456 498 531
Compression Ratio:	20:01, 19:01
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	0.75 1.1 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280

[illegible]