## 12HP 25 HP Air Cooled Diesel Engine 10HP Air Cooled Diesel Motor

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Price:
- Delivery Time: 15-20 workd

China

GET

ISO CE

- Payment Terms:
- Negotiable 15-20 workdays LC, T/T, PayPal, Western Union, Smallamount payment, Money Gram



## **Product Specification**

•	Туре:	Single Cylinder, Vertical, Four-stroke, Direct Injection, Air-cooled
•	Borexstroke:	73x59mm, 78x62mm, 86x72mm
•	Displacement:	247ml, 296ml, 418ml
•	Compression Ratio:	20:01, 20:01, 19:01
•	Rated Power(kw/rpm):	3.5/3000-3.8/3600 3.68/3000- 4/3600 5.7/3000-6.3/3600
•	Rated Power(hp/rpm):	4.8/3000-5.2/3600, 5.0/3000-5.4/3600, 7.8/3000-8.6/3600
•	Rated Speed(rpm):	3000/3600
•	Lowest Rotation Speed At Zero Load:	≤1300r/min
•	Lubricating System:	Pressure Splashed
•	Starting System:	Recoil Start/electric Starter
Rotation Direction(face T The Output Axle ):		Anticlockwise
	Fuel Type:	0#/aummar) 10#/wintar) 0E#(ahilloada)

## GET192F 10hp 12hp 25hp Air Cooled Diesel Engine Air Cooled Diesel Generator

An air-cooled diesel generator is a type of generator that utilizes an air-cooling system to dissipate the heat generated during its operation. It consists of a diesel engine coupled with an alternator to produce electrical power. Here are some key features and advantages of air-cooled diesel generators:

Cooling System: Instead of relying on a liquid cooling system with a radiator and coolant, air-cooled generators use a combination of cooling fins and fans to circulate air and cool the engine. This design eliminates the need for a separate cooling system, making the generator more compact and easier to maintain.

Durability and Reliability: Air-cooled diesel generators are known for their robustness and reliability. The absence of a liquid cooling system reduces the risk of coolant leaks and associated maintenance issues. They are often chosen for applications where durability and continuous operation are critical.

Low Maintenance: Air-cooled generators generally require less maintenance compared to liquid-cooled generators. With no coolant to monitor or replace, there are fewer maintenance tasks involved. However, regular maintenance such as oil changes, filter replacements, and general inspection are still necessary to ensure optimal performance.

Portability: Due to their compact design and lighter weight compared to liquid-cooled generators, air-cooled diesel generators are more portable and easier to transport. This makes them suitable for applications where mobility is required, such as construction sites or outdoor events.

Cost-effectiveness: Air-cooled generators generally have a lower upfront cost compared to liquid-cooled generators. They are often more affordable to purchase and maintain, making them a popular choice for smaller-scale applications and budget-conscious users.

Ambient Temperature Considerations: It's important to note that air-cooled generators are affected by ambient temperature. In hot climates or high-temperature conditions, their cooling efficiency may be reduced, potentially impacting their performance. Adequate ventilation and proper placement of the generator are necessary to ensure optimal cooling in such environments.

		1 0		GET195F
Туре	Single cylinder, vertical, four-stroke, direct injection, air- cooled	Single cylinder,	Single cylinder, vertical, four-stroke,	Single cylinder, vertical, four-stroke,
	88.75*90mm	75*77mm	92*75mm	95*75mm
Displacem ent		19:01cc	19:01cc	19:01cc
Compressi on Ratio	6.7/3000	7.8/3000	6.5/3000	8.1/3000
Rated Power (KWipm)	7.2/3600	7.3/3600	8.2/3600	8.7/3600
Rated Power (HPIIPm)	9.8/3600	10.3/3600	112/3600	11.8/3600
Rated Speed (rpm)		3000/3600	-	
Lowest rotation speed at zero loed		1300		
Lubricatin g system		Pressure splashad	Pressure splashad	Pressure splashad

When considering an air-cooled diesel generator, it's essential to assess your power requirements, intended applications, and environmental conditions to determine if it aligns with your needs. Additionally, consulting with a reputable generator supplier or manufacturer can provide you with specific information on available models and their capabilities.



B.Z.Tgar		#EL. E.E. BE. ER. RIVER Inge office, vehicl, bur-shok, and redon, an-costo			
10're houdeste	and a	19789	30'00	4972	
HE Department	- 16	545	296	48	
Editt Compression Faste-		20101	4041	1901	
WEIDE Robel Frank	enton	0.5/9000 3.8/9800	1.00/0000 4/3000	5.1380 6.3380	
使見記事 field Porty	High	4.9/2000 5.2/2000	1.01000 1.41000	1.8380 8.6380	
BEFER Tales Speed	494	3000 7 3600			
84.048.000.048 Lower solder speecial zero had		- 1888			
R#htt.ubroinciumen		BX 182 Person-quarter			
Bibliot Swing union		EGESTER Focul Semiantic state			
Michiel (CROMINE) Relation developments to the subplexies		Bittl Associate			
WART Task Spec		Co 1231-1011031-3201080108010801110000000-10010ande1-320100000010000			
BARRE Furlish saysily	- L	2.8	11	8.6	
Relation products (main		200-2/3008	676.10000 005.50000	275 13000 381,513000	
REAR Lide of the		60 gaos or S46 199-36, 199-46			
RPB98 Lide of Ispecty	1. L	4.9		1.05	
Giblight Rill Starting maker separatly	1.10	5V08/8			
8424088 Darging preside sayasily	W. 8	12/ 834			
ROATE failery spacing	V. m	101 201m	GV 234e	12V 354v	
REPORT Contract development (L = PLo14)	ma	430'400'488	48014801018	307407343	
## to wept	14		10		

GET Wuxi Guangertai Power Machinery Co.,Ltd

🔇 13813650506 🖸 2415819289@qq.com 🙆 dieselenginepumps.com