

7500T Silent Diesel Generator 72 DB Quiet Portable Diesel Generator

Basic Information

. Place of Origin: China Brand Name: **GET** ISO CE · Certification: · Price: Negotiable • Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-Payment Terms:

amount payment, Money Gram



Product Specification

. Rated Frequency: 50hz 60hz

Rated Output(kw): 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3 • Max Output (kw): 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7

220V Or As Request • Rated Voltage (V):

• Rated Currency (A): 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/

27.2 28.6

Rated Rotation Speed

(r/min):

3000 3600

• Phase No.: Single Phase

Power Factor: F Insulation Grade: • Pole Number: 2

Excitation Mode: Self-excitation & Constant Voltage (AVR)

Panel Type: General Panel . Receptacle: Two Receptacles

Cammantian Dala

Product Description

GET7500T Silent Diesel Generator Red Portable Silent Generator

A quiet diesel generator is a type of generator that is designed to produce less noise compared to conventional diesel generators. They are specifically engineered with noise-reducing features and technologies to minimize the sound output during operation. Here are some key aspects and features that contribute to the quiet operation of a diesel generator: Soundproof Enclosure: Quiet diesel generators often come equipped with a soundproof enclosure or housing. The enclosure is constructed using materials that absorb and dampen the noise generated by the engine and other components. This helps to reduce the overall noise level emitted by the generator.

Muffler and Exhaust System: A quiet diesel generator is typically fitted with a high-quality muffler and an efficient exhaust system. The muffler dampens the noise created during the combustion process, while the exhaust system is designed to minimize vibration and noise transmission.

Vibration Isolation: Noise reduction in diesel generators also involves isolating vibrations from the engine and other moving parts. Special rubber mounts or anti-vibration pads are used to dampen vibrations, preventing them from being transmitted as noise.

Engine Design: Quiet diesel generators may incorporate advanced engine designs and technologies that reduce noise emissions. This can include optimized combustion processes, improved engine insulation, and reduced mechanical friction. Cooling System: The cooling system of a quiet diesel generator is designed to operate efficiently while producing minimal noise. This may involve the use of silent fans, insulated coolant lines, and carefully designed airflow pathways to reduce noise associated with cooling.

associated with cooling.	
Rated Frequency:	50hz 60hz
Max Output (kw):	2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7
Rated Currency (A):	11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6
Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	164 150 150 153 161
Noise Level (7m):	72 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	296 418 456 498 531
Compression Ratio:	20:01, 19:01
Starting System:	Electric Start
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 30Ah
Fuel Tank Capacity (L):	15
Rated Output(kw):	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	945*555*700
Working Assorting Weight (kg):	179 185 186 186 187
Structure Type:	Silent Type
Cylinder Nobore X Stroke (mm):	1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600
Lubrication System:	Pressure Splashed
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	1.1/ 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280
	-

Quiet diesel generators are commonly used in settings where noise reduction is crucial, such as residential areas, outdoor events, and locations with noise restrictions. They offer the advantage of providing reliable power while keeping noise disturbances to a minimum. However, it's important to note that even quiet diesel generators will still produce some level of noise during operation, albeit significantly reduced compared to standard generators.



ere senso	DETHOOF	OFFINANT	GETPOWE	DETMONE	GETOMOET	
BE BE Cuturity and Pro 1			9 6			
BE BIS Pales maked (1697)	23 28	65 48	48 83	87.40	40 63	
BA-BIS Man, materal CHAFT	37.30	10 13	8.2 8.8	63.60	48.37	
EEEE Pater volume (5)	SOVERHIE PRE SOV or as request					
BERGE Paled coverage (4.)	71.9 12.7	204 218	21.8 22.7	20.9 272	272 28.6	
BESIDNE Photocoloxistics speed Colean 1	200 200					
BIE Place NO.	BIRTON JOSE					
SHEET Flower Sector 1 Dog -0 7						
BIR RIS Incustration Concer-						
DE THE HARDE	*					
BMETIC Excitor mate	BERES (Barell) Set excitation & conduct voltage parties					
ENERG Ford Non	# BIRS Green Front					
Bit Bill Pacytoria	NY ORDER DIS Ton receptation					
ROSES Consister pais	8 Nitrod					
BROC SIV DESIVORAN	MIRRIES Connector pole rupol					
#R.F-# Grand diseases (L. v'W-xH) Cres.)	947/507/500	845100768	985 555 790	840'000'700	86/55/76	
BE Dy wight I to I	104	160	150	163	182	
SPACE RESIDENCE AND ADDRESS OF THE PARTY OF	179	185	186	100	160	
CONTROL SAN	- 19	79	19	39	79	
BRIDES TRANSPORT	Shell bur					
SIDERS Drave Motor	DETITIES OFFICERA OFFICES DETITIES OFFICES					
ESPECIAL Drune Type	98, 1	C. Mr. 3rt. Aven	E. Strigte sylholic, vertical, fo	our-offstale, dreed spectron, is	H-100H	
NJEB-IEBNER DYNOU'RD, cook i Broke (mm.)	1-79'90	1-96'72	1-88779	1-975	1-8175	
BME Displacement mr	296	4.0	450	498	500	
Bilt to Bis No. many Fasted prover	3.56/3000 43800	5,700004,93800	5:5/9008 F.(2/9800)	1.03000 5379000	8.190004.7080	
Elifet Compression ratio	100.04	19101	1891	1994	19101	
RROS Labrication system	EXTURBER Property splanted					
Bildrift (Searing system	Right District start					
MIRRIE FLAT NOT	04 (EX)-104 (SX)-564 (GB) SS deal(4 (some)-64 (side)-84 (stitus) deal					
BURGAN S Later of Second	CD makes SM 604 ML 100 AD					
READ Liverage (L.)	1.4	1.65	146	1.86	1.65	
BUT SUFFER Barbon motor capacity (7-445)	120 5,369	127 09/8	SIV EMP	120 1,200	127 1,269	
BASINES Charging generator capacity (V-A)	50V 6.34	100 8.36	SEV AMA	SN 8.34	129 8.56	
DRAME Indeposports (v-An)	100 3046 10V 3046					
BERRE Necomment of State	+260	<280	<380	+290	< 380	
MERRE Purton specty (L.)	- 9	19	10	70	15	
INSTRUMENT COMPANIES CONTROL STORY NO. 1 NO. 1	- 11	1		- 1		

GET Wuxi Guangertai Power Machinery Co.,Ltd

13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA