China GET

ISO CE

# 6.3KW 8.5KW Diesel Engine Fire Pump Low Pressure Diesel Fire Fighting Pump

## **Basic Information**

• Place of Origin:

**G**ET

- Brand Name:
- Certification:
- Model Number:
- Price:
- Delivery Time:
- Payment Terms:





## **Product Specification**

• Туре:	Diesel Clean Water Pump
<ul> <li>Suction/discharger Port Diameter Mm(inch):</li> </ul>	50(2'). 80(3'). 100(4'). 150(6')
• Discharge Capacity m <sup>3</sup> /h):	30 40 110 150
<ul> <li>Total Head Lift:</li> </ul>	25m 26m 22m 20m
• Self-priming Time (s/4m):	80 120 180 180
<ul> <li>Max Suction Head:</li> </ul>	8m 8m 8m 6m
• Rotation Speed (r/min):	3600
<ul> <li>Noise Level Db(A)/7m):</li> </ul>	85
• Overall Dimension(mm):	510x455x640. 560x455x655. 650x470x700 770x574x785
Dry Weight:	44kg 50kg 71kg 95kg
Engine Model:	GET173F GET178F GET186FA GET192F
Rated Power:	2.8kw 4kw 6.3kw 8.5kw
• Fuel Consumption G/kw.h:	288 285 281 281
	0.47 000 440 400

### **Product Description**

### Low Pressure Diesel Engine Fire Pump Diesel Engine Pumps

Agriculture: Electric diesel engine pumps are used in agricultural applications for irrigation, water transfer, and crop spraying. They can efficiently move water from a water source to fields or irrigation systems, ensuring proper hydration for crops. Construction: In construction sites, electric diesel engine pumps are employed for dewatering excavations, draining flooded areas, and supplying water for concrete mixing and dust control. These pumps can handle large volumes of water and are capable of operating in rugged and remote construction environments.

Mining: Electric diesel engine pumps play a crucial role in mining operations. They are used for dewatering mines, pumping water out of underground tunnels, and transferring water across mine sites. These pumps are designed to handle abrasive and corrosive fluids commonly encountered in mining applications.

Model	JBC6/10	
Туре	vacuum pump	
Max.Flow(T/h)	48	
MAX.Lift(m)	60	
Rated Speed(rpm)	3600	
Water Shot Height	35m	
Engine	190F	
Maximum Suction Height(m)	7	
Self-priming Time(S)	20	
Discharge Port Diameter(mm)	65	
N.W/G.W(KG)	91/100	
Dimensions(mm)		
Loading Qty(20GP/40HQ)		
Model	JBC6/15	
Туре	vacuum pump	
Max.Flow(T/h)	54	
MAX.Lift(m)	80	
Rated Speed(rpm)	3600	
Water Shot Height	35	
Engine	192	
	7	
Maximum Suction Height(m)	μ <sup>μ</sup>	
Maximum Suction Height(m) Self-priming Time(S)	20	
Self-priming Time(S)	20	
Self-priming Time(S) Discharge Port Diameter(mm)	20 65	

13813650506

GET Wuxi Guangertai Power Machinery Co.,Ltd

2415819289@qq.com 🕑 dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA